

DRW-250e

With Premium Controller



- Operates on 12V
- Powerful motor
- Only 13 kg / 25lb
- 300m/1000' Ø5mm rope capacity
- Clutch for neutral
- Easy to use
- Emission free



Technical Specifications	DRW-250e with Premium Controller	
	Winch	Battery box with controller
Size [L x W x H]	44x44x30cm 17x17x12"	42x32x26cm 16x13x10"
Drum external diameter	28cm 11"	-
Drum internal width	28cm 11"	-
Drum capacity [Ø5mm rope]	300m 1000'	-
Drum capacity [Muletape® WP1250]	400m 1,300'	-
Maximum pipe segment length	300m 1000'	-
Power supply	12V	12V
Nominal Current	20A	20A
Maximum Peak current	100A	100A
Speed control	Full variable 0-100%	Full variable 0-100%
Pulling speed [empty-full drum]	0.8-1.2m /s 2.5-4'/s	-
Nominal Pulling Force [empty-full drum]	50-30kg 110-66lb	-
Maximum Pulling Force [empty-full drum]	80-50kg 175-110lb	-
Cable winding mechanism	-	-
Horizontal rope guide roll	YES	-
Total weight [excl. rope]	13kg 25lbs	3kg 7lbs (excl battery)
Recommended battery type (not included)		Sealed lead acid 12V 20 to 55Ah



SCAN
ME!